

HNE - HiCAFS Portable Firefighting



HiCAFS 02/035



HiCAFS 02/050

Technology

HNE systems are ready for immediate use and easy to handle. Professionals all over the world rely on HNE. The systems are characterised by the use of high grade material and components which, of course, also meet highest demands concerning resistance

of corrosion and pressure. Quality and operation convince by efficiency, performance and durability as much as by a well-balanced cost-benefit-ratio. The equipment is optimally adjusted to the rough conditions of the daily mission.

Technical Data

		HiCafs 02/035	HiCafs 02/050
Filling volume		35 Litre	50 Litre
Operating pressure		34 bar	34 bar
Flow rate		40 l/min	40 l/min
Operating time		appr. 53 sec.	appr. 75 sec.
Temperature range		+5°C - +60°C	+5°C - +60°C
Discharge length		18 m	18 m
Extinguishing agent	Standard	Water and AFFF 6% concentrate	
	Frost proof	under preparation	
Propellant	Compressed air	5 litre / 300 bar	6 litre / 300 bar
Hose length		10 m	10 m
Approval EN 1866		n/a	P3-2/03
Ratings	AFFF 6%	IV B	IV B
Electrical	EN 1866	Upto 1.000 Volt / 3 m distance	
Weight	empty	appr. 48 kg	appr. 55 kg
	filled	appr. 83 kg	appr. 105 kg
Dimensions	height	670 mm	705 mm
	width	610 mm	610 mm
	length	660 mm	660 mm
Pressure vessel		CE 0036	CE 0036
Pushbar		height adjustable	
Other		Other hose length optional	

Vimpex Limited

Star Lane, Great Wakering, Essex SS3 0PJ England
 Tel: +44 (0) 1702 216999 • Fax: +44 (0) 1702 216699
 E-mail: sales@vimpex.co.uk
www.rescue-tools.co.uk

VIMPEX
 Advancing Rescue Technology